



## Leaking pipe entry fitting repair system without disconnecting the pipework



- Repairs carried out without pipe disconnection
- No excavation or breaking up concrete
- Permanently bonded with FastFuse in 40 minutes
- Compatible with ethanol and ethanol blend fuels
- Wide variety of options and sizes
- Adaptable to all sump, pipe and fitting combinations
- Leaktesting is possible immediately after installation

# Leaking pipe entry fitting repair system without disconnecting the pipework

The CGH Split-Repair Fittings are designed to replace failed, leaking entry fittings and reducer boots. These fittings and boots are easily installed with FastFuse bonder, without disconnecting pipes or breaking up concrete.

The CGH Split-Repair Fittings offer a solution for all types of sump, pipe and fitting combinations that require repair.

Customized parts specification support is as simple as filling in the Repair Specification Worksheet at the CGH website where you can also add pictures of the sump and the existing fittings.

CGH will reply by e-mail with a complete list of parts and materials for the repair.

Please also visit the CGH website to consult the training page for more details.



**Split-Repair Fitting Options are available for all types of sump, fitting and pipe combinations!**



CGH Belgium nv  
Rijksweg 10 C  
B-2880 BORNEM  
Tel.: +32 (0)3 459 80 76  
E-mail: [info@cghbelgium.com](mailto:info@cghbelgium.com)

[www.cghbelgium.com](http://www.cghbelgium.com)

iFix-EN- 20160511  
Non contractual document